



Dimension Ranges			
(A) (width)	18, 21 and 24 in	(C) (height)	43.5 in
(B) (depth)	18 in	(D) (height)	54.5 in

Cabinet:

- Powdercoated 18 gauge cold rolled steel; multi-piece shell and frame design.

Door Construction:

- *Front/Back:* 12 Mil. Seamless polymer-covered front; melamine back (Frost in color).
- *Core:* 45 lb. LEED IEQ compliant MDF board, 3/4 inch thick. All composite wood material to meet CARB P2 emission std of CARB reg. 91320.2.
- *Hinges:* Manufacturer's standard Blum®, concealed, self-closing, 110 deg. opening, nickel-plated metal, clip-on mount, three adjustment points.
- *Pulls:* 128 mm pull offering for Serenity, Transcend, Cascade, and Pinnacle Style Panels; Integrated front pull design (Cove style); Recessed clear snap-on handle w/ interchangeable color strips (Renew style).

Drawers:

- *Deep Drawer Construction:* One piece molded polystyrene drawer bodies w/rounded corners; (Frost in color).
- *Front/Back:* 12 Mil. Seamless polymer-covered front; melamine back (Frost in color).
- *Core:* 45 lb. LEED IEQ compliant MDF board, 3/4 inch thick. All composite wood material to meet CARB P2 emission std of CARB reg. 91320.2.
- *Slide:* Manufacturer's standard Accuride Aero (100 lb. capacity) ball bearing slides.
- *Slides:* Include inter-lock to prevent more than more than one drawer from being opened at the same time (Reduce tipping hazard).
- *Slides are soft close.*
- *Pulls:* 128 mm pull offering for Serenity, Transcend, Cascade, and Pinnacle Style Panels; Integrated front pull design (Cove style); Recessed clear snap-on handle w/ interchangeable color strips (Renew style).

Adjustable Shelving:

- Powdercoated 18 gauge cold rolled steel, painted to match cabinet color; manufacturer's standard die cast zinc support clips.

Locks:

- *Doors:* Manufacturer's standard Timberline, individually mounted, cam style lock removable lock plug; locks keyed alike with two keys per lock.
- *Drawers:* Manufacturer's standard Timberline lock body with removable lock plug with 14 gauge cold rolled steel pivoting lock bar for central lock system; locks keyed alike with two keys per lock.

Casters

- Manufacturer's standard Shepherd Caster Corp®, 4 in twin wheel design with elastomeric treads, stem mounting; locking wheel.

ArtHalf