# midmark®

Install Guide
Casters *[9A554]*

Applies to Models:
630 (-010 /-011 /-020 /-021)

Language of origin: English

Restrictions:
Do not install casters with rotational base.

Step 1: Unplug chair power cord.

Caution
This chair weighs approximately 475 lb. (215 kg).
Use an assistant when lifting chair.

Step 2: Remove leveling screws.
A) Lift foot end of chair.
B) Position a 4 x 4 support under base.
C) Remove two leveling screws.

MA8969i

**4" X 4" X 24"
Support**

TP200 Rev. A

Step 3: Install foot end casters.
A) Push down brake lever to lock caster.
B) Thread caster into base.
C) Tighten caster firmly to secure.

MA8970i

Brake Lever

⚠️ **Caution**
To prevent injury, lock foot end casters before performing Step 4.

Step 4: Install head end casters.
A) Lift head end of chair.
B) Position a 4 x 4 support under base.
C) Remove two leveling screws.
D) Push down brake lever to lock caster.
E) Thread caster into base.
F) Tighten caster firmly to secure.

Note: Reference illustration on page one.

⚠️ **Caution**
To prevent injury, always lock casters before performing any procedures.

MA8972i

To UNLOCK caster(s)...
Lift up on brake lever.

To LOCK caster(s)...
Press down on brake lever.

⚠️ **Caution**
To prevent injury, *never* move or reposition chair with patient aboard.

TP200 Rev. A

midmark®