


INSTALLATION MANUAL

Midmark Care Exchange

6281 Laptop Wall Mounted Workstation



Weight Capacity
0-8 lbs.

TABLE OF CONTENTS

Tools Required / Installation Warnings / Disclaimer / Safety Warning / Adjustment Notification 3

Mounting Height..... 4

How to Install Toggles 5

Mounting Surface 6 - 7

Pivot Limiter..... 8

Optional Extension Arm 9

Main Arm Installation

 Installation direct to Wall Ear

 Installation to the Extension Arm 9

Laptop Station Installation 10

Tension adjustment - Workstation Flip 10


Counterbalance the Arm 11

Tray Leveling Adjustments 11

Cable Management 12

Accessory Track Mount Installation 12

TOOLS REQUIRED



Allen Wrenches: 1/4", 7/32", 3/16" and 1/8"
Socket Wrench: 7/16"
Drill Bit: 1/8" and 1/2"

INSTALLATION WARNINGS:

- Read the entire instruction manual before beginning any installation or assembly.
- The installer must verify that the entire wall safely supports the combined weight of all the attached equipment and hardware.
- Improper installation of this product may cause extensive property damage or serious personal injury, either during or after installation.
- Warning: Applied loads in excess of 80 lbs. on the work surface may result in product failure, causing the work surface to fall and possibly resulting in personal injury.

DISCLAIMER:

- The manufacturer and/or distributor will bear no responsibility for any damages of any kind arising from any improper installation of this product.
- Because wall construction varies widely and the ultimate method of mounting/installing is out of the manufacturers or distributors control, it is imperative that the installer consult with local engineering, architectural, or construction personnel to ensure the wall is constructed properly to code and will handle the applied load.
- Through improper installation or excessive applied load, the workstation can be pulled out of the wall by force, taking with it a large section of drywall. In no way will the manufacturer or distributor be held liable for any damage to the monitor, property or personal injury should an outside force either intentionally or unintentional be applied to the monitor or monitor mounting bracket causing it to pull off the wall.

SAFETY WARNING:

- California installations may require specific anchorage and additional supports. Check with local authorities for codes in your area. Other seismic states will have similar regulations.
- Prior to drilling, verify the location of any electrical wiring with in the wall. An electrical short can kill or create serious injury and fire hazard both during and after installation.
- OSHPD certificate available upon request.



ADJUSTMENT NOTIFICATION:

- Routine maintenance checks and adjustments are suggested to properly support the quality and optimal performance of this product. Refer to adjustment suggestions on last page of booklet, or contact your distributor for further detailed information.
- Over tightening of bolts during installation or adjustments may damage the product and affect the function and warranty.


MOUNTING HEIGHT

POSITIONING WALL EAR

If installing directly to drywall (hollow wall applications) please note the bottom of the wall ear must be positioned between 8"-14" from the bottom of the track.





- Loosen, but do not remove 4 corner bolts
- Place in desired position
- Level the wall ear
- Tighten bolts to 200 in-lbs force to ensure the unit is securely fastened





We recommend having the wall ear installed at the following heights which comfortably accommodates the majority of users in seated or standing positions. 23" desired low height.

31" FROM FLOOR TO BOTTOM OF WALL EAR 27" FROM FLOOR TO BOTTOM OF WALL EAR




HOW TO INSTALL TOGGLERS


Use a level and ensure track is flush, flat and snug to the wall. Mark hole locations prior to drilling and install toggler bolts in appropriate locations.



Use bolts provided to secure track to the wall. Refer to the reference guide on pages 6 and 7.






OR



MOUNTING SURFACE

DIRECT TO DRYWALL




34" TRACK - 10 outer holes



CRITICAL: The wall ear must be positioned between 8"-14" from the bottom of the track.

STEEL STUD




34" TRACK - 5 inner holes



NOTE: Bolts are to be placed in the horizontal center of the 2"x 4" Steel Stud.

CONCRETE WALL (block)



34" TRACK
- 5 inner holes



NOTE: Bolts must pass through concrete block. Bolts must not pass through mortar bed between blocks nor through the web within the blocks. When attaching to concrete blocks, only one bolt per cell allowed.

WOOD STUD



34" TRACK - 5 inner holes



NOTE: Screws are to be placed in the horizontal center and must penetrate at least 2" into the wood stud.

CONCRETE WALL (solid)

34" TRACK - 5 inner holes
Concrete hardware not provided




3/16" x 2-1/4" lg. Min. Tapcon® Concrete screws (not provided) to pass through the wall track as per screw manufacturers intructions.
NOTE: Pre drilled holes to be created using Tapcon® drill bit for 3/16"x2-1/4"lg. concrete screws to a Min. hole depth of 2-1/2" into concrete slab.


PIVOT LIMITER

This item is to be positioned (if required) before installing the extension arm or main arm to the wall ear.


LIMITER HOLES ON THE EXTENSION ARM




LIMITER HOLES ON THE MAIN ARM



PIVOT LIMITER VIEW FROM UNDERSIDE




Limits 90° right rotation




Position pins as shown to limit rotation to the right

Allows 180° rotation




Position pin at 12:00 to prevent the arm from coming in direct contact with the wall on either side

Limits 90° left rotation



Position pins as shown to limit rotation to the left

Limits total rotation





Position pins at 3:00 & 9:00 for a full rotation lock out

OPTIONAL ITEMS

OPTIONAL EXTENSION ARM


Installation direct to Wall Ear. This is an optional item and not included in all configurations.

For further information please contact your distributor.




MAIN ARM INSTALLATION

MAIN ARM INSTALLATION DIRECT TO WALL EAR




INSTALLATION OF MAIN ARM TO THE EXTENSION ARM

Main arm to be installed once extension arm has been secured.




LAPTOP STATION INSTALLATION

Use the 7 bolts provided to assemble laptop station to the arm.



TENSION ADJUSTMENT - Workstation Flip




COUNTERBALANCE THE ARM

Once all after-sale technology is installed, perform the following adjustments to ensure the arm raises and lowers as required and does not freely drift up or down.

ATTENTION:
Arm must be held in the downward position while making adjustments.

- STEP 1**
Remove the trim cap at the back of the arm.
- STEP 2**
Use the 1/4" Allen Key to turn the middle bolt at the back of the arm. Turning the bolt clockwise decreases the spring force reducing the counter balance load. Turning the bolt counterclockwise increases the spring force increasing the counter balance load.
- STEP 3**
Adjust the middle bolt until the arm counter balance is acceptable.
- STEP 4**
Replace the trim cap at the back of the arm.




TRAY LEVELING ADJUSTMENTS (Left to Right)

Tray adjustment is to be made after all technology has been installed.

- STEP 1**
Remove the trim cap at the back of the arm.
- STEP 2**
Use the 3/16" Allen Key to turn the top bolt at the back of the arm. Turn the bolt until the tray is level.
- STEP 3**
Confirm that surface is level with spirit level.
- STEP 4**
Replace the trim cap at the back of the arm.

ATTENTION:
Arm must be parallel to the work surface and swiveled 90° to the base when adjusting.



CABLE MANAGEMENT

After the technology has been installed, ensure there is enough slack in the cables from the keyboard and mouse along with any other peripherals.

STEP 1

Use a #2 Phillips screwdriver to remove the screws securing the cable management tray & plate.

STEP 2

Remove the steel insert from the cable management tray. Note orientation of steel insert in cable management tray.

STEP 3

Lay all cables (e.g. power, VGA and mouse cables) into the cable management tray.

STEP 4


Re-assemble steel insert from STEP 3 with counter sinks to the bottom of the cable management tray and notch at the back.

STEP 5

Re-attach the cable management tray & plate with the screws removed in STEP 1.

STEP 6


Route cables through the cable cover.




ACCESSORY TRACK MOUNT INSTALLATION

This item is optional and not included in all configurations.

TRACK-MOUNT BAR CODE HOLDER



Slide the Scanner carriage onto the track.



Tighten fully and test the Track-Mount Bar Code Holder to see if it remains in place prior to installing any technology.

